

All packages come with 7' spacing braces, walkboards and guardrails.

Catalog No	Part No	Description	10 ft RT7-P10	15 ft RT7-P15	20 ft R7-P20
B-FS55S	10012-01	Step Frame 5'x5' B Size, S Lock, 27 3/4" Spacing	4	6	8
B7H27	03014	Brace - 7' Spacing, Hole End	4	6	8
B-IN	08002	9" Insert - B Size	8	12	16
SN	06003	2" Snap Pin	8	12	16
RC	06004	2" Rivet & cotter	8	12	16
B-C8	26003	8" Cast Iron Caster - B Size	4	4	8
B-BC57	05001-01	Squaring Brace - B Size	1	1	1
B-GRZ5E	20009-01	End Guard Rail - B Size	2	2	2
GRZ7S	20001	Side Guard Rail	2	2	2
GRZTB7	21003-01	Toe Board 7'	2	2	2
WBP119x7	35303	19" x 7' Walkboard	3	3	3
B-OR	25003-01	30" Outrigger	0	0	4
Working Height			17 ft	22 ft	27 ft
Set up full platforms at the following heights:			6' or 11'	6', 11' or 16'	6', 11', 16' or 21'

Meets federal OSHA standards. Check your state and local codes.

Packages are made up of standard parts making it easy to add accessories. We recommend purchasing additional walkboards to make setup easier and to create platforms at additional heights.

Full platforms consist of 3 walkboard and will measure 5' x 7'.

For outside or uneven surface add the leveling package. The 20 ft tower (R7-P20) requires 2 leveling packages (RT-PL). See below.

Leveling Package - RT-PL			
Item No	Part Number	Description	Qty
B-LJX	23012	Leveling Jack Extension	4

SPECS:
Tube size (O.D.): B, 1-5/8"
Lock type: S
Lock space: 27 3/4"

S Lock Shown
 Use braces with
 hole ends.





20' Rolling Tower



15' Rolling Tower



10' Rolling Tower