



**Snappy**<sup>TM</sup>



Maximum Capacity  
1000 lbs. Distributed

Meets or Exceeds  
Requirements of American National Standards  
Institute ANSI CODE A 10.8

Meets or Exceeds  
OSHA Requirements

Patent No's  
6,471,003  
6,761,247



SP-6  
6' Snappy Unit.  
Platform Height 27" - 6'  
Dimensions: 29"W x 74"L  
Unit Weight 235 lbs.



SP-6D  
6' Snappy Double Unit with Guardrail & Outriggers.  
Platform Height 27" - 12'  
Dimensions: 29"W x 64"L  
Unit Weight 386 lbs.



SP-6G  
6' Snappy Unit with Guardrail.  
235 lbs.

SP-GRS6  
Guardrail only.  
Unit Weight 90 lbs.

Triple Unit Also Available.  
Call Factory for Details.





User friendly squeeze-lock is spring loaded to maintain the locked position at all times except when released for adjustment. A locking G-Pin is provided to prevent unintentional release. Additional snap pin is provided as a dual locked scaffold system.



Steel edge banding protects all four sides of the exterior-grade plywood work platform without using rivets, screws or staples. Hand holds on each side provide ease in handling. Platform is held in place with spring-loaded hold down clips.



5" swivel casters with dual brakes that prevent both rolling and swiveling when brake lever is depressed. Caster includes a 2" snap pin to attach the caster to the scaffold.



Use 4 outriggers on Snappy Scaffolds above 6' high. Outrigger includes 2 snap pins and 1 thumb screw. Casters and base plates sold separately.



Legs are independently adjustable, allowing you to have a stable work surface on uneven ground or on stairways.

## POWER SNAPPY

MOTORIZED WORK PLATFORM

### MOTORIZED WORK PLATFORM

Model M (18706)  
Platform height: 24" - 60"  
Overall dimensions 31" x 60"  
Deck Capacity 500 lbs.  
Unit Weight 300 lbs

Electric powered, environmentally friendly, no emissions and virtually no noise. You're able to work indoors or out. Productivity is enhanced by reducing the time wasted moving devices and climbing up and down.

It's the ideal work platform for: Electricians, painters, maintenance personnel, schools, hospitals, hotels, office buildings and more.




# 6' Snappy Utility Scaffold

Description	Item No.	Part No.	Weight
Single Unit	SP-6	18006-0102	145 lb
Single Unit w/ Expanded Metal Deck	SP-6X	18019-0102	155 lb
Single Unit w/ Guard Rail	SP-6G	18007-0102	235 lb
Double Unit w/ Guard Rail & Outriggers	SP-6D	18008-0102	386 lb
Triple Unit w/ Guard Rail & Outriggers	SP-6TR	18075	523 lb
39" Add-On Unit Pkg (2 ladders, 2 braces)	SP-6AD3	18026-0102	75 lb
65" Add-On Unit Pkg (2 ladders, 2 braces)	SP-6AD6	18032-0102	92 lb
6' Guard Rail Set (2 pcs)	SP-GRS6	18137-02	90 lb
Narrow Outrigger Pkg (4 pcs)	SP-NORP	18015-02	25 lb
Wide Outrigger Pkg (4 pcs)	SP-WORP	18104-02	60 lb
5" Caster	SP-C5	18086	5 lb
Adjustable Leg w/ Rubber Pad	SP-ADJLEG	18044-01	3 lb
39" Ladder Frame	SP-L39	18012-01	15 lb
65" Ladder Frame	SP-L65	18025-01	25 lb
6' Plywood Platform	SP-P6	18004	27 lb
6' Expanded Metal Platform	SP-X6	18017-01	30 lb
6' Hinged Plywood Platform	SP-PH6	18030	40 lb
6' Platform Arm Brace	SP-B6	18013-02	22 lb
G Pin Replacement Kit	SP-GL	18080	1 lb


	Plt. Ht.	Max Wlk Ht.	Overall Ht.
SP-6 Single	27"-6'	13'	6'
SP-6 w/ GR	27"-6'	13'	9'6"
SP-6D Double	27"-12'	18' 6"	15'
SP-6T Triple	27" - 17'	24'	20'6"

## PLEASE NOTE:

Granite Industries recommends, and some states limit, the free-standing tower height to be 3 times the minimum base dimension. OSHA codes allow 4 times the minimum base dimension. Please consult your state and local codes for compliance information.




SP-6AD3  
39" Add-on unit



SP-6AD65  
65" Add-on unit




SP-GRS6  
Guard Rail Set




SP-P6  
6' Plywood Platform




SP-L39 / SP-L56  
Ladder Frame




SP-WB  
72" Wide Base



SP-B6  
6' Arm Brace



SP-NORP WT 25 lb  
Narrow Outrigger



SP-WORP WT  
Wide Outrigger



SP-C5  
5" Caster